



IPP 3-Ply Waterproofing Membrane Protection System

Description: 3-ply waterproof sealing membrane to be applied under ceramic tiles for protection of floors and walls from moisture migration and accessories

Fabric

Raw material	
TNT spunbonded	

Internal layer

Raw material			LDPE
Color			BLUE
Thickness	EN 1849-2	in	.007874

Composite material

Thickness at 2 kPa	EN 1849/2	in	001968504
--------------------	-----------	----	-----------

Waterproofing	EN 1928 B		1,5bar/24 h No leakage
Watertightness in the installed conditions	PG AIV F 3,8		No leakage
sd (23°C-50% U.R.)	EN 1931	ft	>196.8503
Water vapour transmission	ASTM E96-13	oz/yd2	.118124
Pull out test dry conditions	EN 1348	psi	0.0000580152

Chemical resistance	EN 1847-EN527-3		Resistant to alkali and acids
	ANSI 118,10		Resistant to fungi and microorganism

Mechanical resistance in the installed conditions	ASTM C627		Extra heavy commercial rating
---	-----------	--	-------------------------------

Standard dimensions

Width		ft	3.3'
Length		ft	98.5'
Rolls per pallet			30

Information given in this data sheet is to the best of our knowledge true and correct, however new research results and practical experience can lead up to revisions performed without notice. No guarantee or liability can be drawn from the information mentioned herein. Furthermore, is not our intention to violate any patents or licences.



Instacoat Premium Products, LLC

5920 Huron Avenue, Oscoda, MI 48750 Tel. 877.552.6724 - Fax 586.932.3328 - e-mail: info@instacoat.com - www.instacoat.com

Rev 2